

SAFETY DATA SHEET.

Issuing date 07-Jan-2015

Revision Date 09-May-2022

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name RP1600 RUST PREVENTIVE (MOLDER CHOICE)

Recommended use of the chemical and restrictions on use

Product code F01489

Product Type Extremely Flammable Aerosol
Synonyms None

Supplier's details

Recommended Use Protective Coating against rust and corrosion.

Uses advised against No information available

Manufactured For: PCS Company 34500 Doreka Drive Fraser, MI 48026 PHONE;1-800-521-0546 M-F 8-5 PM	Manufacturer American Jetway Corporation 34136 Myrtle Street Wayne, MI 48184-0126 Phone:(734) 721-5930
--	---

Emergency telephone number

Chemical Emergency Phone NumberCHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification


Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness.
 Causes damage to organs (Eyes, Skin,, Respiratory System, Central Nervous System, and Kidneys) through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.
 Extremely Flammable Aerosol
 Contains gas under pressure; may explode if heated



Appearance Slightly Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves, protective clothing, eye protection,, face protection.
 Wash face, hands and any exposed skin thoroughly after handling.
 Do not breathe dust, fumes, gas, mist, vapors, spray.
 Use only outdoors or in a well-ventilated area.
 Do not eat, drink or smoke when using this product.
 Keep away from heat, sparks, open flames, hot surfaces - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

If exposed or concerned : Get medical advice ,attention.
 Specific treatment (see first aid on this label).
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice, attention

IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice, attention.
 Take off contaminated clothing and wash it before reuse.
 IF INHALED : Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor, physician if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
 Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-47-8	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	15-25
HEPTANE	142-82-5	10-20
METHYLCYCLOHEXANE	108-87-2	1-10
TOLUENE	108-88-3	1-10
N-OCTANE	111-65-9	1-10
2-BUTOXYETHANOL	111-76-2	1-10
PETROLEUM DISTILLATES	8052-41-3	1-10
CYCLOHEXANE	110-82-7	0.1-1.0
ETHYLENE GLYCOL	107-21-1	<0.1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water for 15 minutes and seek medical advice.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to target organs through prolonged or repeated exposure. Harmful or fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Foam. Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of

can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
HEPTANE 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
METHYLCYCLOHEXANE 108-87-2	TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³	IDLH: 1200 ppm TWA: 400 ppm TWA: 1600 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
N-OCTANE 111-65-9	TWA: 300 ppm	TWA: 500 ppm TWA: 2350 mg/m ³ (vacated) TWA: 300 ppm (vacated) TWA: 1450 mg/m ³ (vacated) STEL: 375 ppm (vacated) STEL: 1800 mg/m ³	IDLH: 1000 ppm Ceiling: 385 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 75 ppm TWA: 350 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
PETROLEUM DISTILLATES 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
CYCLOHEXANE 110-82-7	TWA: 100 ppm	TWA: 300 ppm TWA: 1050 mg/m ³ (vacated) TWA: 300 ppm (vacated) TWA: 1050 mg/m ³	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m ³
MINERAL OIL, DEWAXED	ACGIH TLV: 5 mg/m ³ (oil mist)	OSHA PEL: 5 mg/m ³ (oil mist)	-

64742-65-0			
ETHYLENE GLYCOL 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m ³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Safety glasses with side-shields. Tightly fitting safety goggles.
- Skin and body protection** Chemical resistant apron. Protective gloves.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Slightly Hazy	Odor Threshold	
Color	Dark Amber		

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	-96.4 °C / -141 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.738	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%) 75.44

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Causes skin irritation.
Ingestion	Harmful and may be fatal if swallowed and enters airways and lungs.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
HEPTANE 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
METHYLCYCLOHEXANE 108-87-2	> 3200 mg/kg (Rat)	> 86700 mg/kg (Rabbit)	-
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
N-OCTANE 111-65-9	-	-	> 23.36 mg/L (Rat) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
PETROLEUM DISTILLATES 8052-41-3	-	> 3000 mg/kg (Rabbit)	-
CYCLOHEXANE 110-82-7	= 12705 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9500 ppm (Rat) 4 h
ETHYLENE GLYCOL 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)	-

Information on toxicological effects

Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Causes damage to target organs through prolonged or repeated exposure.. Harmful or fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Irritating to eyes.
Irritation Causes eye and skin irritation . May cause respiratory irritation.
Sensitization No information available.
Germ cell mutagenicity Not a germ cell mutagen.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.
Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ systemic toxicity (repeated exposure) Causes damage to Target Organs listed below through prolonged or repeated exposure.
Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects Eyes, Skin, Respiratory System, Central Nervous System, and Kidney.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3165 mg/kg
ATEmix (dermal) 14904 mg/kg
ATEmix (inhalation-gas) 87069 mg/l
ATEmix (inhalation-dust/mist) 68.2 mg/l
ATEmix (inhalation-vapor) 637 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas	-	-

		96h flow-through		
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
HEPTANE 142-82-5	-	375.0 mg/L LC50 Cichlid fish 96h	-	-
METHYLCYCLOHEXANE 108-87-2	-	2.07 mg/L LC50 Oryzias latipes 96h semi-static	-	-
TOLUENE 108-88-3	12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static 433 mg/L EC50 Pseudokirchneriella subcapitata 96h	11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static 12.6 mg/L LC50 Pimephales promelas 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 54 mg/L LC50 Oryzias latipes 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
N-OCTANE 111-65-9	-	-	-	0.38 mg/L EC50 water flea 48h
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h
CYCLOHEXANE 110-82-7	500 mg/L EC50 Desmodesmus subspicatus 72h	23.03 - 42.07 mg/L LC50 Pimephales promelas 96h static 24.99 - 44.69 mg/L LC50 Lepomis macrochirus 96h static 3.96 - 5.18 mg/L LC50 Pimephales promelas 96h flow-through 48.87 - 68.76 mg/L LC50 Poecilia reticulata 96h static	-	-
ETHYLENE GLYCOL 107-21-1	6500 - 13000 mg/L EC50 Pseudokirchneriella subcapitata 96h	14 - 18 mL/L LC50 Oncorhynchus mykiss 96h static 40000 - 60000 mg/L LC50 Pimephales promelas 96h static 16000 mg/L LC50 Poecilia reticulata 96h static 27540 mg/L LC50 Lepomis macrochirus 96h static 40761 mg/L LC50 Oncorhynchus mykiss 96h static 41000 mg/L LC50 Oncorhynchus mykiss 96h	-	46300 mg/L EC50 Daphnia magna 48h

Persistence and degradability

Bioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
HEPTANE	4.66

142-82-5	
TOLUENE 108-88-3	2.7
N-OCTANE 111-65-9	5.18
2-BUTOXYETHANOL 111-76-2	0.81
CYCLOHEXANE 110-82-7	3.44
ETHYLENE GLYCOL 107-21-1	-1.93

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even after use. Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	x	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	x	X	X	X	X
HEPTANE	X	X	X	X	X	X	X	X
METHYLCYCLOHEXA NE	X	X	X	X	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
N-OCTANE	X	X	X	X	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X
CYCLOHEXANE	X	X	X	X	X	X	X	X

ETHYLENE GLYCOL	X	X	X	X	X	X	X	X
-----------------	---	---	---	---	---	---	---	---

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- CHINA - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	5.16395	1.0
2-BUTOXYETHANOL - 111-76-2	111-76-2	3.16552	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
CYCLOHEXANE 110-82-7	1000 lb			X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
CYCLOHEXANE 110-82-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Ethylene Glycol CAS # 107-21-1) is considered a Proposition 65 chemical for developmental only when ingested. The purpose of this product is not for ingestion. NO warning for Ethylene Glycol is required for this product.



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental /1-10%
ETHYLENE GLYCOL - 107-21-1	Developmental (ingested)/<0.1%

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
HEPTANE 142-82-5	X	X	X
METHYLCYCLOHEXANE 108-87-2	X	X	X
TOLUENE 108-88-3	X	X	X
N-OCTANE 111-65-9	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X
PETROLEUM DISTILLATES 8052-41-3	X	X	X
CYCLOHEXANE 110-82-7	X	X	X
ETHYLENE GLYCOL 107-21-1	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards -
HMIS Health Hazard 2* Flammability 4 Physical Hazard 1 Personal protection B
 Chronic Hazard Star Legend *Chronic Health Hazard/ Repeated or prolonged exposure may cause central nervous system damage*

Prepared By American Jetway Corporation
 34136 Myrtle Street
 Wayne, MI 48184-0126
Issuing date 07-Jan-2015
Revision Date 09-May-2022

Revision Note
 (M)SDS sections updated 1 2 3 9 11 14 15

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet